

Material Safety Data Sheet

WEARLON® Wetlander Top Coat-A

Trade Name As Used On Label

PLASTIC MARITIME CORPORATION
P.O. BOX 2131 - TRAVER ROAD
WILTON, NY 12831 USA
518-587-7624

PREPARED BY: J. R. SMITH
March 2011
24 HR. EMERGENCY# 800-424-9300
(INTL. EMERGENCY# 703-527-3887)

I. PHYSICAL DATA

Boiling Point: >212°F.

Specific Gravity (H₂O=1): >1.0

Vapor Pressure (mm Hg and Temperature): < 21mm Hg @ 20°C

Melting Point: N/A

Vapor Density (Air=1): Lighter than air

Evaporation Rate (Butyl Acetate=1): Slower than Butyl Acetate

Solubility in Water: Miscible

II. MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS - Chemical Name & Common Names	%	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)				
Epoxy Silicone emulsion Cas# 025068-38-6	54
2-Propoxyethanol Cas# 2807-30-9	2
... Not Established				
Non-Hazardous Ingredients	44			
TOTAL	100			

III. FIRE AND EXPLOSION HAZARD DATA

Flash Point and Method Used: 200°F TCC

Auto-Ignition Temperature: N/A

Flammability Limits in Air, % by Volume: N/A

LEL: N/A

UEL: N/A

Extinguisher: Dry foam, Carbon Dioxide

Special Fire Fighting Procedures: None

Unusual Fire and Explosion Hazards: None

IV. HEALTH HAZARD DATA

Primary Routes of Entry: Inhalation, Ingestion, Skin Absorption

Effects of Overexposure: Possible skin rash. May damage eyes.

Emergency and First Aid Procedures: Wash hands and eyes with soap and water. If ingested drink plenty of water. Call physician.

V. REACTIVITY HAZARD DATA

Stability: ☐ UNSTABLE ☒ STABLE

Conditions to Avoid: Open flame, spark, and high heat.

Incompatibility (Materials to Avoid): Strong acids, bases, amines can cause polymerization

Hazardous Decomposition Products: may include carbon dioxide or carbon monoxide

Hazardous Polymerization: ☒ MAY OCCUR ☐ WILL NOT OCCUR

Conditions to Avoid:

VI. CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (Specify Type):

Protective Gloves: **Chemical resistant gloves**

Eye Protection: **Chemical resistant goggles**

Ventilation to be Used:

☐ Local Exhaust

☒ Mechanical (general)

☐ Special

☐ Other

Other Protective Clothing and Equipment: **Wash after using.** Segregate all cleaning apparatus.

Hygienic Work Practices: Avoid contamination of skin.

VII. PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES

Steps to be Taken if Material is Spilled or Released: Wash with water. Dike all spills; absorb with inert material and collect for disposal.

Waste Disposal Methods: Incinerate or use biological treatment in accordance with Federal, State and Local Regulations.

Precautions to be Taken in Handling and Storage: Mix before using and store at room temperature above 40°F,

DO NOT FREEZE.

NON-REGULATED